

## Let the CAT Catch a STYLE

Yanhong Liu, Cincinnati Children's Hospital Medical Center, Cincinnati, OH  
Justin Bates, Cincinnati Children's Hospital Medical Center, Cincinnati, OH

### ABSTRACT

Being flexible and highlighting important details in your output is critical. The use of ODS ESCAPECHAR allows the SAS® programmer to insert inline formatting functions into variable values through the DATA step, and it makes for a quick and easy way to highlight specific data values or modify the style of the table cells in your output. What is an easier and more efficient way to concatenate those inline formatting functions to the variable values? This paper shows how the CAT functions can simplify this task.

### INTRODUCTION

In your Output Delivery System (ODS) output, you can define an escape character (for display purposes, we will use the caret ^ in this paper) with the ODS ESCAPECHAR = statement. The ODS escape character allows you to use inline formatting functions. These functions enable you to set the style for text strings like ODS text fields, titles and footnotes. By using string concatenation functions, the inline formatting functions also can be inserted into individual variable values in the DATA step and thus provide the ability to modify and enhance the text style within data cells. Below is a simple SAS data set (Table 1) where each Var1 value was concatenated with an inline function to create the Var2 value:

Var1	Var2
A Dagger	A Dagger <sup>{dagger}</sup>
An Alert	<sup>{style [foreground=red]}An Alert</sup>
A Superscript	A Superscript <sup>{super 1}</sup>

**Table 1. A SAS Data Set with Concatenating Inline Formatting to the Variable Values**

If a PROC PRINT were used on the data set above, the result in the ODS output (RTF destination) would be the following:

Obs	Var1	Var2
1	A Dagger	A Dagger†
2	An Alert	An Alert
3	A Superscript	A Superscript <sup>1</sup>

**Output 1. RTF Output fromTable1**

There are two general ways to concatenate strings together. One way is to use the CAT family of functions (CAT, CATS, CATT, and CATX functions) which were introduced in SAS® Version 9. The other way to concatenate strings together is to use the concatenation (double vertical bar) operator, ||, with functions such as TRIM and/or LEFT, but this method can be less compact than using one of the functions in the CAT family of functions. For example,

Without CAT Function: `var2=trim(left(var1))||"^{dagger}";`

With CAT Function: `var2=cats(var1,"^{dagger}");`

In this paper, we will first briefly review some of the inline functions that can be used with ODS ESCAPECHAR, then explore the features of CAT family functions, and finally we will demonstrate how the CAT functions are an efficient and easy way to catch the inline formatting functions for creating the style you desire.

## ODS INLINE FORMATTING FUNCTION: GIVE YOUR OUTPUT A STYLE

Inline formatting functions enable you to modify styles in titles and footnotes, text strings, and table cells; however, before you can perform inline formatting with ODS, you must first use the ODS ESCAPECHAR statement to define an escape character, such as:

```
ODS ESCAPECHAR='^';
```

The general format for the inline style syntax is:

```
^{function-name<<arg-1 <arg-2<arg-n>>>>}
```

Where "^" is the ODS escape character, "{" and "}" are the inline style grouping characters, arg-1 ... arg-n are the arguments to the given function, and function-name is the name of the inline function.

Below is an example that uses the STYLE function in a title:

```
Title 'The Title is ^{style [color=blue]blue}';
```

This example would produce the following result:

*The Title is blue*

ODS ESCAPECHAR is designed to be used in output designated for the Output Delivery System. The inline formatting functions will affect all open destinations except for the LISTING destination. But some functions can only be used with certain destinations, like the PAGEOF function, ^{PAGEOF} , which only works with the RTF and TAGSETS.RTF destinations for showing the Page X of Y.

Table 2 lists the functions that work for most destinations. (All are available in SAS® V9.2)

Function Syntax	Description	Example	RTF Output (Generated from: ODSINLINE.SAS)
^{dagger}	Generates the Greek dagger sign †	MyValue^{dagger}	MyValue†
^{nbspspace <count>}	Count is the number of spaces that you want to insert; default value is 1	MyValue1^{nbspspace 2}MyValue2	MyValue1 MyValue2
^{newline <count>}	Count is the number of lines that you want to insert; default value is 1	MyValue1^{newline 1}MyValue2	MyValue1 MyValue2
^{sigma}	Produces the Greek Sigma sign σ	MyValue^{sigma}	MyValueσ
^{style <style-element><[attributes]> formatted text}	The style attributes or elements remain in effect until they are overridden by another style	^{style [foreground=red] MyValue}	MyValue
^{sub subscript-text}	The subscript-text can be a numeric, alphanumeric, or a character value. This value is written below and immediately to one side of another character	MyValue^{sub 1}}	MyValue <sub>1</sub>
^{super superscript-text}	The superscript-text can be a numeric, alphanumeric, or a character value. This value is written above and immediately to one side of another character	MyValue^{super *}	MyValue <sup>*</sup>
^{Unicode <Hex  name>}	Prints any special character by name or an actual four-place hexadecimal Unicode value.	MyValue1^{Unicode 2265}MyValue2	MyValue1≥MyValue2

**Table 2. Some Inline Functions that can be used with ODS ESCAPECHAR**

## PROGRAM: ODSINLINE.SAS

```
data odsinline;
  length Myvar $200;
  Myvar = "MyValue^{dagger}";
  output;
  Myvar = "MyValue1^{nbspspace 2}MyValue2";
  output;
  Myvar = "MyValue1^{newline 1}MyValue2";
  output;
  Myvar = " MyValue^{sigma}";
  output;
  Myvar = " ^{style [foreground=red] MyValue}";
  output;
  Myvar = " MyValue^{sub 1}";
  output;
  Myvar = " MyValue^{super *}";
  output;
  Myvar = " MyValue1^{Unicode 2265}MyValue2";
  output;
run;

ods rtf file='odsinline.rtf' notoc_data;
ods escapechar='^';

proc print data=odsinline;
run;

ods _all_ close;
```

Program ODSINLINE.sas creates several observations in which different in-line formatting functions have been added for controlling their styles in the data cells. By using string concatenation functions, the inline formatting can also be inserted into an existing data value in the DATA step; next we will explore the features of the CAT family of functions family to find out why it is the best choice to simplify the concatenation task.

## THE CAT FUNCTIONS: WHAT IS THE CAT DOING?

In SAS you can combine strings of characters together with string concatenation functions. In Version 9, SAS introduced the CAT family of functions (CAT, CATS, CATT, and CATX functions). These string concatenation functions can take the place of two older functions, TRIM and LEFT, when they are paired with the concatenation operator (||).

As shown in the Introduction, the CAT family of functions gives you an easier and more compact way to streamline your SAS code when concatenating character strings. In addition, you can use the CAT functions with the OF operator to refer to an entire group of sequentially numbered variables without listing each one, for example,

Without OF Syntax:	X1  X2  X3  X4 or CAT(X1, X2, X3, X4)
With OF Syntax:	CAT(of X1-X4)

The lengths of the resulting variables created by the two concatenation methods may be different. In a DATA step, if the CAT function returns a value to a variable that has not previously been assigned a length, then the length of that variable defaults to 200 bytes. In contrast, if the concatenation operator (||) returns a value to a variable that has not previously been assigned a length, then the length of that variable is the sum of the lengths of the source variables. It is important to set the length of your variables that you create by using the CAT functions, so that you keep reasonable processing/storage costs while keeping the variable lengths long enough to hold the longest string created by concatenation.

Table 3 shows equivalents of the CAT, CATS, CATT, and CATX functions. The variables X1 through X4 specify character variables.

Function	Equivalent Code	Description
CAT(of X1-X4)	X1  X2  X3  X4	The CAT function simply combines any number of character arguments end-to-end; no leading or trailing blanks are removed from character arguments
CATS(of X1-X4)	TRIM(LEFT(X1))  TRIM(LEFT(X2))   TRIM(LEFT(X3))  TRIM(LEFT(X4))	The CATS function removes both leading and trailing blanks before concatenating arguments.
CATT(of X1-X4)	TRIM(X1)  TRIM(X2)  TRIM(X3)   TRIM(X4)	The CATT function removes only trailing blanks before concatenating arguments.
CATX(SP, of X1-X4)	TRIM(LEFT(X1))  SP   TRIM(LEFT(X2))  SP   TRIM(LEFT(X3))  SP   TRIM(LEFT(X4))	The CATX function removes leading and trailing blanks before concatenating arguments, and inserts delimiters (here SP is the delimiter) between arguments.  Note: if any of the arguments are blank, CATX omits the corresponding delimiter. For example,  CATX ("^", "X", " ", "Y", " ");  produces X^Y.

**Table 3. Equivalent Statements to the CAT Family of Functions**

If the variables X1 through X4 specify numeric variables, some of the equivalents in Table 3 will not apply. Let us see an example below to find out the differences:

**PROGRAM: CATNUM.SAS**

```
data catnum;
X1=1;
X2=23;
X3=456;
X4=7890;
MyVar_Cat=cat(of X1-X4);
MyVar_noCat=X1||X2||X3||X4;
run;
```

```
1 data catnum;
2 X1=1;
3 X2=23;
4 X3=456;
5 X4=7890;
6 MyVar_Cat=cat(of X1-X4);
7 MyVar_noCat=X1||X2||X3||X4;
8 run;
```

NOTE: Numeric values have been converted to character values at the places given by:  
(Line):(Column).  
7:14 7:18 7:22 7:26

NOTE: The data set WORK.CATNUM has 1 observations and 6 variables.

NOTE: DATA statement used (Total process time):  
real time 0.02 seconds  
cpu time 0.01 seconds

**Display 1. SAS Log Produced By Running Program CATNUM.SAS**

VIEWTABLE: Work.Catnum														
	X1	X2	X3	X4	MyVar_Cat					MyVar_noCat				
1	1	23	456	7890	1234567890						1	23	456	7890

**Display 2. SAS Data Set Produced By Running Program CATNUM.SAS**

Alphabetic List of Variables and Attributes			
#	Variable	Type	Len
5	MyVar_Cat	Char	200
6	MyVar_noCat	Char	48
1	X1	Num	8
2	X2	Num	8
3	X3	Num	8
4	X4	Num	8

**Display 3. PROC CONTENTS From The SAS Data Set CATNUM**

The CAT functions can be used with numeric variables without producing a note in the SAS log about numeric-to-character conversion; however, the concatenation operator (||) would produce such a message.

The concatenation operator converts each numeric variable to character by using the default format BEST12., and therefore the resulting variable “MyVar\_noCat” has blanks in it. In contrast, the CAT function uses the format W., where W represents the width of the each variable X1 to X4, which is equivalent to the following two lines of code:

```
length MyVar $200;
MyVar=put(X1,1.) || put(X2,2.) || put(X3,3.) || put(X4,4.);
```

Again, since we didn’t assign the length for the resulting variables MyVar\_Cat and MyVar\_noCat, the length of MyVar\_cat defaults to 200, and MyVar\_noCat has the length of sum of each source variable which is 12\*4=48.

**AN EXAMPLE: LET THE CAT CATCH A STYLE**

We have explored the features and advantages of both inline formatting functions and the CAT family of functions. Now we will demonstrate how to utilize the advantages of the CAT functions to concatenate the inline formatting functions to existing variables in the DATA step.

**SOURCE DATA SET:**

For our example, we made a data set that is a subset of the SASHELP.CARS data set, and we limited the variables and values as shown in the following table:

Variable Name	Variable Type	Variable Values Used In Example
Make	Character	'Cadillac', 'Lexus', 'Mazda', 'Mitsubishi'
Type	Character	'Sedan', 'Sports', 'SUV'
Model	Character	
MPG_City	Numeric	
MPG_Highway	Numeric	

**Table 4. Variables and Values Selected from SASHELP.CARS**

After calculating the average (mean) MPG in the City and MPG on the Highway for each categorized car type, our SAS data set looked like this:

	Make	Model	Type	MPG (City)	MPG (Highway)	highway_mean	city_mean
1	Cadillac	CTS VVT 4dr	Sedan	18	25	27.5	20.5
2	Cadillac	Deville 4dr	Sedan	18	26	27.5	20.5
3	Cadillac	Deville DTS 4dr	Sedan	18	26	27.5	20.5
4	Mitsubishi	Diamante LS 4dr	Sedan	18	25	27.5	20.5
5	Lexus	ES 330 4dr	Sedan	20	29	27.5	20.5
6	Mitsubishi	Eclipse GTS 2dr	Sports	21	28	26.1	19.7
7	Mitsubishi	Eclipse Spyder GT convertible 2dr	Sports	21	28	26.1	19.7

#### Display 4. SAS Data Set of the Example (Partial View)

#### IDEAL OUTPUT:

We wanted to generate a summary report (a WORD file) with output that looked like this:

#### *Comparing both CITY and HIGHWAY MPG*

MAKE	TYPE		
	SUV	Sedan	Sports
Cadillac	Escalade SRX V8	CTS VVT 4dr Deville 4dr Deville DTS 4dr Seville SLS 4dr	XLR convertible 2dr
Lexus	GX 470 LX 470 RX 330†	ES 330 4dr GS 300 4dr GS 430 4dr IS 300 4dr auto IS 300 4dr manual LS 430 4dr	SC 430 convertible 2dr
Mazda	Tribute DX 2.0†	MPV ES Mazda3 i 4dr† Mazda3 s 4dr† Mazda6 i 4dr†	MX-5 Miata LS convertible 2dr† MX-5 Miata convertible 2dr† RX-8 4dr automatic RX-8 4dr manual
Mitsubishi	Endeavor XLS Montero XLS Outlander LS†	Diamante LS 4dr Galant ES 2.4L 4dr† Galant GTS 4dr Lancer ES 4dr† Lancer LS 4dr† Lancer OZ Rally 4dr auto†	Eclipse GTS 2dr† Eclipse Spyder GT convertible 2dr† Lancer Evolution 4dr

† This model has both higher CITY and HIGHWAY MPG than the average for its Type

#### Display 5. Desired ODS RTF Output

In our example summary report, we wanted to list the car models one per line in the Make/Type categorized cell, and we wanted to emphasize or highlight those car models that have both higher CITY and HIGHWAY MPG than the average for their Type. We wanted to do this both by highlighting the car model with a different colored font and by adding a dagger sign at the end of the car model's name.

#### SOLUTIONS:

First, we inserted the inline formatting functions `^{\style [foreground=blue]}` and `^{\dagger}` to those car models which have greater mpg\_city and mpg\_highway than the mean mpg for their Type.

Then, we transposed the data set to one record per make and type. Since each record has a different number of models, some model columns would be blank. The following shows a portion of the transposed data set:

	Make	Type	model1	model2	model3	model4
1	Cadillac	SUV	Escalade	SRX V8		
2	Cadillac	Sedan	CTS VVT 4dr	Deville 4dr	Deville DTS 4dr	Seville SLS 4dr
3	Cadillac	Sports	XLR convertible 2dr			
4	Lexus	SUV	GX 470	LX 470	<span style="color: blue;">^</span> {style [foreground=blue]RX 330}^ <span style="color: red;">^</span> {dagger}	
5	Lexus	Sedan	ES 330 4dr	GS 300 4dr	GS 430 4dr	IS 300 4dr auto

#### Display 6. Transposed SAS Data Set (Partial View)

Next, we used the string concatenation function to join all the non-blank model names along with the inline formatting function `^`{newline} as a delimiter so that the output will have one model per line in the table's cells.

The following table is a portion of the resulting data set:

	allmodel	Make	Type
1	Escalade <code>^</code> {newline 1}SRX V8	Cadillac	SUV
2	CTS VVT 4dr <code>^</code> {newline 1}Deville 4dr <code>^</code> {newline 1}Deville DTS 4dr <code>^</code> {newline 1}Seville SLS 4dr	Cadillac	Sedan
3	XLR convertible 2dr	Cadillac	Sports
4	GX 470 <code>^</code> {newline 1}LX 470 <code>^</code> {newline 1} <span style="color: blue;">^</span> {style [foreground=blue]RX 330} <code>^</code> <span style="color: red;">^</span> {dagger}	Lexus	SUV
5	ES 330 4dr <code>^</code> {newline 1}GS 300 4dr <code>^</code> {newline 1}GS 430 4dr <code>^</code> {newline 1}IS 300 4dr auto <code>^</code> {newline 1}IS 300 4dr manual <code>^</code> {newline 1}LS 430 4dr	Lexus	Sedan

#### Display 7. Inline Formatting Functions Added to the "allmodel" Variable (Partial View)

Finally, we used another PROC TRANSPOSE to make our final SAS data set ready for the ODS output.

#### THE SAS CODE:

The following two sections of SAS code show the differences between using the CAT functions and using TRIM and LEFT with the concatenation operator(`||`) for the concatenation.

```

**The First Concatenation;
data mycars;
  format model $100.;
  set mycars;
  if mpg_city>city_mean and mpg_highway>highway_mean then
  model= "^{style [foreground=blue]"||trim(left(model))||"}"^{dagger}";
run;

**The Second Concatenation;
data mycars;
  length allmodel $350;
  set mycars;
  array arr {*} model;
  do i = 1 to dim(arr);
    if i=1 then allmodel=arr(i);
    else if i>1 and arr(i) ne " " then
      allmodel =trim(left(allmodel))||"^{newline 1}"||arr(i);
  end;
  drop i model; ;
run;

```

#### Display 8. SAS Code Example Without CAT Functions

```

**The First Concatenation;
data mycars;
    format model $100.;
    set mycars;
    if mpg_city>city_mean and mpg_highway>highway_mean then
model= cats("<span style [foreground=blue]> ",model," ", "<span style [foreground=blue]> {dagger}");
run;

**The Second Concatenation;
data mycars;
    length allmodel $350;
    set mycars;
    allmodel = catx("<span style [foreground=blue]> {newline 1}",of model:);
    drop model: ;
run;

```

### Display 9. SAS Code Example With CAT Functions

By comparing the highlighted codes, you can see that by using CAT functions not only did we use fewer statements, we also simplified the logic and made the code more readable and understandable. Especially in the second concatenation, by using the CATX, we didn't have to conditionally determine the value of each model to see if it is blank, since CATX conveniently only adds the inline function `^(newline)` between the non-blank strings.

## CONCLUSION

The inline formatting functions provide a very flexible way to enhance your ODS output. By concatenating those functions to existing variable values through the DATA step, the programmer can better customize the output of data cells. When compared to the original string concatenation method (using `||` with TRIM and LEFT), the CAT family of functions provides an easier and more efficient way to do this task.

## REFERENCES

SAS® 9.3 Output Delivery System: User's Guide, Second Edition

SAS® 9.2 Language Reference: Dictionary, Fourth Edition

Zdeb, Mike. Searching for Variable Values with CAT Functions: An Alternative to Arrays and Loops. Proceedings of the NESUG Users Group, September 2009.

## ACKNOWLEDGMENTS

The authors wish to thank the Data Management Center at Cincinnati Children's Hospital Medical Center for its support, and particularly Matthew Fenchel and Kelly Olano for their helpful feedback.

## CONTACT INFORMATION

Your comments and questions are valued and encouraged. Contact the author at:

Yanhong Liu  
 Cincinnati Children's Hospital Medical Center  
 3333 Burnet Ave.  
 Cincinnati, OH 45255  
 (513) 803-2614  
 E-mail: [Yanhong.Liu@cchmc.org](mailto:Yanhong.Liu@cchmc.org)

Justin Bates  
 Cincinnati Children's Hospital Medical Center  
 3333 Burnet Ave.  
 Cincinnati, OH 45255  
 (513) 803-2756  
 E-mail: [Justin.Bates@cchmc.org](mailto:Justin.Bates@cchmc.org)

SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Other brand and product names are trademarks of their respective companies.

## APPENDIX

The Full SAS Program for the Example:

```
data cars;
set sashelp.cars;
if type in ('Sedan', 'Sports', 'SUV') and make in ('Cadillac', 'Lexus', 'Mazda',
'Mitsubishi');
keep type make mpg_city mpg_highway model;
proc sort; by model;
run;

proc sql noprint;
create table mycars as
    select a.*,b.highway_mean ,b.city_mean from cars as a full join
        (select model, avg(mpg_city) as city_mean format 4.1, avg(mpg_highway) as
highway_mean format 4.1
        from cars
        group by type) as b on a.model=b.model;

quit;

**The First Concatenation;
data mycars;
    format model $100.;
    set mycars;
    if mpg_city>city_mean and mpg_highway>highway_mean then model=cats("^{style
[foreground=blue]",model,"}","^{dagger}");
proc sort; by make type;
run;

proc transpose data=mycars out=mycars(drop=_name_) prefix=model;
    by make type;
    var model;
run;

**The Second Concatenation;
data mycars;
    length allmodel $350;
    set mycars;
    allmodel = catx("^{\newline 1}",of model:);
    drop model: ;
run;

proc transpose data=mycars out=mycars(drop=_name_);
    by make;
    id type;
    var allmodel;
run;

ods listing close;
ods rtf file="mycars.rtf" style=printer;
ods escapechar="^";
OPTIONS NONUMBER NODATE orientation=portrait;

Title "Comparing both CITY and HIGHWAY MPG";

proc report data=mycars
    NOWINDOWS
    SPACING=1
    HEADLINE
    HEADSKIP
    split="|"
```

```
style(header)=[background=lightgrey];

columns (('^S={bordertopcolor=black} ' make) ("TYPE|" SUV Sedan Sports));
define Make /display style={cellwidth=3 cm} style(header)=[bordertopcolor=lightgrey]
"MAKE " ;
define SUV /display left style={cellwidth=5 cm} "SUV";
define Sedan /display left style={cellwidth=5 cm} "Sedan";
define Sports /display left style={cellwidth=5 cm} "Sports";
run;

ods rtf text="^S={font=('Times Roman', 8.5pt, bold) leftmargin=0.48in}^{dagger}This
model has both higher CITY and HIGHWAY MPG than the average for its Type";
ods rtf close;
ods listing;
```